

Magnetic base mounts

Internal magnets with scratch reduction pads


In-stock
Ready to
Ship

Page 1 of 2

A-2148

Construction	Black moulded ABS body, internal magnet and adhesive scratch reduction pad
Diameter	41mm
Height	45mm
Mount thread	M6 x 7mm
Cable	Specify requirements when ordering, must have FME female termination
Connector	FME female one end - required, specify other end termination requirement when ordering
Mounting requirements	Mount onto any flat magnetic metallic surface



MGB

Construction	Black powdercoated steel, internal slotted magnet and adhesive scratch reduction pad
Diameter	105mm
Height	19mm
Mount hole	16.5mm
Compatible mount bases	OB-2 base or OB-4.7 - 5/16"-26 TPI thread XB base - 6mm thread P/N 7994 right-angle UHF female
Mounting requirements	Mount onto any flat magnetic metallic surface



Magnetic base mounts

Internal magnets with scratch reduction pads


In-stock
Ready to
Ship

Page 2 of 2

MGB-GP

Construction	Black powdercoated steel, internal slotted magnet and adhesive scratch reduction pad
Diameter	180mm
Height	20mm
Mount hole	16.5mm
Compatible mount bases	OB-2 base or OB-4.7 - 5/16"-26 TPI thread XB base - 6mm thread P/N 7994 right-angle UHF female
Mounting requirements	Mount onto any flat magnetic metallic surface



A-2845

Construction	Black powdercoated steel, Santoprene coated Tri-magnet mount base
Diameter	180mm
Height	20mm
Mount hole	13mm
Compatible mount bases	any maximum 13mm O.D. bases
Mounting requirements	Mount onto any flat magnetic metallic surface

