

Section 3 Section 3 Vehicle Mount o



ZN3-77-12 Series

Super heavy-duty detachable spring base collinear UHF CB Radio 477 MHz



The ZN3-77-12 series of UHF CB radio antennas are specifically designed for vehicle mounting on trucks or large 4WD's. Offering the highest gain in the range, this antenna will deliver the maximum transmit and receive range suitable for flat ground.

Mounting hardware, connectors and other installation accessories are all available separately.

	ZN3-77-12B	ZN3-77-12W	
Colour	Black	White	
Construction	Coloured fibreglass radome, aluminium ferrule, stainless steel 'barrel' spring base, external coaxial cable and termination		
Frequency range	477 MHz - UHF CB radio		
Bandwidth	476.4125 - 477.4125 MHz - covering all 40/80 channels		
VSWR	<1.5:1		
Tuning	Factory		
Gain	8.1dBi - suits flat terrain such as central Australia		
Maximum power	100 Watts		
Impedance	50 Ohms		
Polarisation	Vertical		
H Plane	360° omnidirectional		
Cable	4.5 metres RG58 low loss, solid core, bottom exit from spring base		
Connector	FME female fitted to cable - for ease of installation		
Adaptor - supplied	FME male to UHF male PL259		
Height	2.1 metres		
Weight	1.6kg		
Mounting hardware order separate	Bullbar: BBM-SS, BBML-SS, BBMXL-SS or BBKB-B Bracket Mounting: GM1, GM2, GM4, GM6		
Mounting position recommended	As high on your vehicle/structure as possible using a 13mm hole or appropriate bracket		
Installation kit contents	3mm Allen key, PVC cap, 8 x cable ties and FME male to UHF male adaptor		
Installation tools required	18mm spanner for spl	18mm spanner for split nut securing to base	









FME male to UHF Male PL259 adaptor




Section 3 Section 3 Vehicle Mount 5




ZN3-77-12 Series











Typical VSWR





Section 3 Vehicle Mount 5



ZN3-77-12 Series





Recommended installation accessories



BBM-SS - wrap around bull bar mount, up to 50mm diameter bull bar tube

16mm mount hole

Requires 10mm spanner



BBMXL-SS - wrap around extra large bull bar mount, up to 76mm diameter bull bar tube

16mm mount hole

Requires 10mm spanner



ATLM series - Adjustable bonnet, boot and door jam mount. 360 rotational and 140 degree adjustment

> 16mm mount hole Black or Chrome

Includes 5mm and 2mm allen kevs



BBML-SS - wrap around extra large bull bar mount, up to 65mm diameter bull bar tube

16mm mount hole

Requires 10mm spanner



BBKB-B - Knock-down antenna mount, powder coated black

16mm mount hole with 5.5mm cable hole



A-6211 - stainless steel fascia/ wall mount bracket 16mm mount hole



Section 3 Section 3 Vehicle Mount 5



ZN3-77-12 Series

Super heavy-duty detachable spring base collinear UHF CB Radio 477 MHz



Vehicle Mounting locations Best/Recommended location for mounting Suitable mounting locations Not suitable mounting locations