

## Section 3a Hand Portable



## ZYUE-WX-2400 series

90 degree swivel whip ISM2.4/WiFi/WLAN



The ZYUE-WX-2400 series of whips have the added ability to be either set straight, or on a 90 degree bend for those space saving requirements.



The ZYUE-WX-2400F and ZYUE-WX-2400F-RPSMA are both designed for WiFi use using the ISM2.4 frequency range.



Adaptors, patch leads, water proofing and other installation accessories are all available separately.

	ZYUE-WX-2400F	ZYUE-WX-2400F-RPSMA*
Construction	Black moulded whip, 90 degree swivel chrome connector	
Frequency range	ISM2.4/WiFi/WLAN 2.4-2.5GHz	
Bandwidth	Full frequency range	
VSWR	<2.0:1	
Tuning	Factory	
Gain	5.5dBi	
Impedance	50 Ohms	
Maximum power	50 Watts	
Connector	SMA male plug connector as base	Reverse polarisation SMA male plug connector as base
Polarisation	Vertical, or 90° vertical to your equipment	
H Plane	360° omni-directional	
Height	220mm	
Weight	26grams	
Mounting	SMA male plug fits to any SMA female jack terminated device.	Reverse SMA male plug fits to any reverse SMA female jack termination device
Mounting position	Mount as high on your structure as possible. If using on a hand-held device, ensure device is not enclosed within metallic material or within a	







SMA male termination in ZYUE-WX-2400F

metallic lined structure.