



RG214/U

**Double braid shielded, stranded core
50 Ohm coaxial cable**


In-stock
Ready to
Ship

Our RF MAX brand of double shielded, 50 Ohm RG214/U coaxial cable offers equivalent or improved construction and performance to "other" brands available.

RG214/U is commonly used in test leads and quality installation requiring Low PIM and cross talk.

This coaxial cable is available in 100m or 300m roll, please consult ZCG for more information.



RG214/U (7808)	
Order code 100m roll	7808-100
Order code 300m roll	7808-300
Centre conductor	Silver plated copper, 7 strand, 2.24mm
Dielectric	Solid polyethylene (PE), 7.25mm
1st braid coverage	96%, Tinned copper braid
2nd braid coverage	98%, Tinned copper braid
Jacket	Black PVC, 1.10mm thick, 10.8mm outside diameter
Mechanical specifications	
Minimum bend radius	Static: 55mm Dynamic: 162mm
Weight	18.5kg per 100 metres
Operating temperature	-40°C to +85°C
Electrical specifications	
Impedance	50 Ohm
Frequency	DC~6GHz
Nominal capacitance	100 pF/m
Velocity of propagation	66%
Sparker test	4,000 VAC
Dielectric strength	Conductor to shield : 10,000 VDC



Attenuation figures on following page...



RG214/U

Double braid shielded, stranded core
50 Ohm coaxial cable


In-stock
Ready to
Ship

Attenuation	Per 100 metres	Maximum power
100MHz	5dB	1028 Watts
200MHz	9dB	727 Watts
300MHz	12dB	593 Watts
400MHz	14dB	514 Watts
500MHz	16dB	460 Watts
600MHz	18dB	420 Watts
800MHz	21dB	353 Watts
850MHz	22dB	353 Watts
900MHz	23dB	343 Watts
1GHz	24dB	325 Watts
1.8GHz	35dB	242 Watts
2GHz	38dB	230 Watts
2.4GHz	43dB	210 Watts
3GHz	50dB	188 Watts
4GHz	61dB	163 Watts
5GHz	72dB	145 Watts
6GHz	82dB	133 Watts

