

7/16" DIN connectors

Suits RG213 to 1-5/8" foam dielectric cables

Page 1 of 2


In-stock
Ready to
Ship
* Signifies build to
order item

716DINF213



7/16" DIN female
clamp connector
For RG213/RG8

Tri-metal plated
Low P.I.M.

716DINF1250SF



7/16" DIN female
clamp connector
1/2" super flexible
cable,
2 kW max power

Tri-metal plated
Low P.I.M.

716DINF1250



7/16" DIN female
clamp connector
1/2" flexible cable,
2 kW max power

Tri-metal plated
Low P.I.M.

716DINF7850



7/16" DIN female
clamp connector
7/8" flexible cable,
2 kW max power

Tri-metal plated
Low P.I.M.

716DINF1580*



7/16" DIN female
connector
1-5/8" flexible cable,
2 kW max power

Tri-metal plated
Low P.I.M.

[7/16" DIN males on following page...](#)

7/16" DIN connectors

Suits RG213 to 1-5/8" foam dielectric cables

Page 2 of 2


In-stock
Ready to
Ship
* Signifies build to
order item

716DINM213



7/16" DIN male
crimp connector
For RG213 cable

Tri-metal plated
Low P.I.M.

716DINMRG214*



7/16" DIN male
crimp connector
For RG214 cable

Tri-metal plated
Low P.I.M.

716DINMRG214-C*



7/16" DIN male
clamp connector
For RG214 cable

Tri-metal plated
Low P.I.M.

716DINM400*



7/16" DIN male
crimp connector
For RU400 cable

Tri-metal plated
Low P.I.M.

716DINM400-C



7/16" DIN male
clamp connector
For RU400 cable

Tri-metal plated
Low P.I.M.

716DINM1250SF



7/16" DIN male
clamp connector
1/2" super flexible
cable, 2 kW max power

Tri-metal plated
Low P.I.M.

716DINM1250



7/16" DIN male
clamp connector
1/2" flexible cable
2 kW max power

Tri-metal plated
Low P.I.M.

716DINM7850



7/16" DIN male
clamp connector
7/8" flexible cable,
2 kW max power

Tri-metal plated
Low P.I.M.

716DINM1580*



7/16" DIN male
clamp connector
1-5/8" flexible cable,
2 kW max power

Tri-metal plated
Low P.I.M.

716DINRAM400



Right-angle
7/16" DIN male
crimp connector
For RU400 cable

Tri-metal plated
Low P.I.M.

716DINRAM1250SF



Right-angle
7/16" DIN male
clamp connector
1/2" super flexible
cable, 2 kW max power

Tri-metal plated
Low P.I.M.

716DINRAM1250



Right-angle
7/16" DIN male
clamp connector
1/2" flexible cable,
2 kW max power

Tri-metal plated
Low P.I.M.